



DESCRIPTION:
MATERIAL:
THREAD:
USE TEMPERATURE:
FOOD CONTACT:
INNER DIAMETER:
NECK DIAMETER:
HEIGHT:
INTERIOR SEAL:

COMPLET DISCHARGE VALVE NW50/ 2" BSPM
POM, LLD-PE, PP, PA66-GF30, SI
NW50 MALE FOR DIN11851 FITTINGS
-20°C to +130°C - Steamable @ 130°C 1,5 Bars
FDA AND 10/2011 CE
50mm
N/A
121mm
Silicone

All films and fitments comply with European and FDA food contact material requirements

DISCLAIMER

- 1-It is customer's responsibility to check product compatibility
- 2-Storing Conditions of empty bags 4°C to 40°C away from direct sunlight ,toxic products or heat sources
- 3-The information contained herein is presented in good faith.However Pusa-Pack s.l. makes no warranty of any kind,either expressed or implied,including those of merchantability and fitness of purpose



DESCRIPTION:
MATERIAL:
CONNECT:
FOOD CONTACT:
DIMENSION:
FLOW:

ELBOW WITH PERFORATED CAP NW50
PE + SILICONE
R2" / BSP - NW50, 76 x 1/6
FDA & 10/2011 CE
63mm x 110mm
49 mm

All films and fitments comply with European and FDA food contact material requirements

DISCLAIMER

1-It is customer's responsibility to check product compatibility
2-The information contained herein is presented in good faith. However Pusa-Pack s.l. makes no warranty of any kind, either expressed or implied, including those of merchantability and fitness of purpose